

DK-28e



主要参数 PRINCIPAL PARTICULARS

Fuel oil/燃油		HFO (重油) 700-180mm ² /s/50℃		Diesel oil/ 船用柴油	
Speed/转速	r/min	720	750	720	750
Frequency/频率	Hz	60	50	60	50
6DK-28e	Eng.kW	1990	1990	1990	1990
	Gen.kW	1870	1870	1870	1870
8DK-28e	Eng.kW	2635	2635	2635	2635
	Gen.kW	2500	2500	2500	2500

注：基于电机效率为94%，具体机组功率由发电机效率决定。
 Note: Based on nominal generator efficiencies of 94%. The final power of D/Gs is determined by generator efficiency.
 具体尺寸根据具体电机型号确定，以下尺寸仅供参考
 The below dimension: only reference. The final dimensions are determined by the type of generator.

Specifications/主要规格

结构 Configuration		直列 In-line	
缸径 Bore	mm	280	
冲程 Stroke	mm	390	
转数 Eng.revs.	r/min	720	750
活塞速度 Piston speed	m/s	9.4	9.8
平均有效压力 Mean eff. press	MPa	缸数/No. of cyl.	
		6	8
爆发压力 Max. combust press	MPa	2.30	2.29
		17.7	17.7

尺寸与重量 DIMENSION & WEIGHT

毫米:mm

尺寸标记 Mark	A	B	C	D	E	F	G	H	J	Dry Weight		
										Eng	Gen	Total
6DK-28e	6825	3710	2235	1230	6100	1300	2065	1095	2580	18.0	9.9	35.0
8DK-28e	7865	3830			6780					3440	23.0	11.8

